


SP90

称重传感器 Load cells



电子台秤、配料秤、包装秤、动态检测系统、台秤
Electric platform,blending scale,packing scale,dynamic testing system,platform scale

TECHNICAL PARAMETER|Exc+(红,Red);Sig+(绿,Green);Sig-(白,White);Sig-(蓝,Blue)

额定载荷 Rated Load	50,100,200,300kg	工作温度范围 Operating Temp Range	-30~+70℃
灵敏度 Sensitivity	2.0±0.01mV/V	安全过载 Safe load limit	120%F.S
综合误差 Total error	±0.03%F.S	极限过载 Over load limit	150%F.S
蠕变（30分钟） Creep(30min)	±0.03%F.S	推荐激励电压 Recommendexcitation	10~12V DC
零点平衡 Zero balance	±1%F.S	最大激励电压 Maximumu excitation	15V DC
零点温度影响 TCO	±0.03%F.S/10℃	密封等级 Protection Class	IP66
输出温度影响 TC SPAN	±0.03%F.S/10℃	材质 Construction	合金钢Alloy Steel
输入阻抗 Input resistance	400±20Ω	电缆 Cable	
输出阻抗 Output resistance	352±3Ω		Length:8m
绝缘电阻 Insulation resistance	≥5000MΩ		Diameter: φ 5mm