

PRODUCT INFORMATION



HANGZHOU KURTIN METAL & HARDWARE CO., LTD

Contact person: Allan Kim E-mail: allan.kim@kurtin.cn
 Head office: room 801, unit 1, building 3, zhidi Mansion,
 xiaoshan district, hangzhou city, zhejiang province, China.

Tel:+86 17767111197 Fax:+86 571-22828661 Cell: +86 17767111197 website:www.kurtin.cn

 <p>24 hours response 48 hours solution provide</p> <p>Structural bolt</p>	<p>Structural bolt with large hex head Specification: 1/2" to 1 1/2", M16-M36 Standard: ASTM A325/A325M, ASTM A490/A490M, DIN6914, JISB1186(F10T) ect. Finish: Black, Dacromet. Hot dip Gal and ect.</p>	 <p>24 hours response 48 hours solution provide</p> <p>Torshear type TC bolt</p>	<p>Tor-shear type bolt Tensile Control Bolt/Tor-shear Type bolt Standard: ASTM F1852, F2280, JSS II09, A325/490 TC Model: M16-M36, 5/8"-1-1/2" Grade: 10.9s, S10T Finish: Black, Dacromet, Hot Dip Gal</p>
 <p>24 hours response 48 hours solution provide</p> <p>Welding stud</p>	<p>Welding Stud Welding stud with ceramic ferrule Standard: ISO13918, AWS D1.1, GB10433, JIS B1198 Material: 1015A 1018 Size: M10-M25, 3/8"-1" Finish: Plain</p>	 <p>24 hours response 48 hours solution provide</p> <p>Stud bolt</p>	<p>B7 Stud bolt Stud bolts Standard: ASTM A193 B7_ASTM A194 2H ASTM A193 B7M_ASTM A194 2H Inch Size: 1/2"-2" LENGTH: 4"-12" Finish: Plain, Black, Hot dip galvanized ect.</p>
 <p>24 hours response 48 hours solution provide</p> <p>Foundation bolt</p>	<p>Foundation bolt Anchor bolt(L type and J type) Standards: DIN, AS, GB Size: M6-M56, 1/4"-2" Material: Ms steel, 45# steel Grade: 4.8, 8.8, 10.9 Surface: plain, Z/P, hot dip galvanizing, blackening</p>	 <p>24 hours response 48 hours solution provide</p> <p>Normal hex bolt</p>	<p>Normal hex bolt, nut and washers Standard: DIN7990 DIN933, din931, DIN960, DIN961, A307, Size: M6-m56, 1/4"-2" Grade: 4.8 6.8 8.8 10.9 12.9 Material: Carbon Steel Finish: Plain; zinc; Hot Dip Gal.</p>
 <p>24 hours response 48 hours solution provide</p> <p>Hot Dip Gal. Series.</p>	<p>Hot dip Gal. Bolt Series. Standard: DIN7990 DIN933, din931, DIN960, DIN961, A307, Size: M6-m56, 1/4"-2" Grade: 4.8 6.8 8.8 10.9 12.9 Material: Carbon Steel Finish: Hot Dip Gal.</p>	 <p>24 hours response 48 hours solution provide</p> <p>Washers</p>	<p>Flat washer Standards: DIN125A, DIN9021 non- standard Size: M6-M56, 1/4"-2" Material: Ms steel, 45# steel Grade: MS Steel, HV steel Surface: plain, Z/P, hot dip galvanizing, black</p>